



No. : <b>T4.SPEC.601.3.B</b> SHEET NO. : A/1	<b>BROAD SPECIFICATIONS</b>  <b>4R810TA2</b> 47.8kW@1800RPM	<b>SECT.</b>  <b>A</b>	 Enriching Lives
---	--	------------------------------	--

**BROAD SPECIFICATIONS OF 4R810TA2 ENGINE FOR EMEGENCY STANDBY GENERATING SET APPLICATION**


S. NO.	PARAMETER	UNIT	VALUE
1.1	Engine Model	--	4R810TA2
1.2	Engine Family	--	JKOEL3.24TAX
1.3	Emission compliance	--	US EPA TIER-III
1.4	Engine cooling	--	Water cooled
1.5	Bore x Stroke	mm x mm	96 x 112
1.6	No. of cylinders	--	4 Cylinder Vertical Inline
1.7	Total displacement	cc	3240
1.8	Valves per cylinder – intake/exhaust	--	1/1
1.9	Compression Ratio	--	16.5 ± 1:1
1.10	Firing order (starting from flywheel end)	--	1-3-4-2
1.11	Combustion system	--	Direct Injection
1.12	Aspiration	--	Turbocharged & charge air cooled
1.13	Engine crankcase vent system	--	Closed crankcase vent System
1.14	Rated speed	rpm	1800 ± 5
1.15	Rated Brake Power output (Production Tolerance: ± 5%)	hp (kW)	65 (47.8)
1.16	Maximum high idle speed	rpm	1805
1.17	B.M.E.P	bar	10.1
1.18	Brake Specific fuel consumption (corresponding to gross power under NTP conditions, after 125 hrs. of engine de-green cycle) (Production Tolerance: + 5%)	100 % LOAD	163
		75 % LOAD	165
		50 % LOAD	178
		25 % LOAD	190
1.19	Type of governing / Speed governor	--	Isochronous / Electronic

Prepared by  <b>NRS</b>	Checked & approved by  <b>VMT/ YVA</b>	Revision No.  <b>00</b>	Date  <b>26/10/2018</b>	Issued by  <b>CRE / KOEL</b>
-------------------------------	--	-------------------------------	-------------------------------	------------------------------------

No. : <b>T4.SPEC.601.3.B</b> SHEET NO. : A/2	<b>BROAD SPECIFICATIONS</b>  <b>4R810TA2</b> 47.8kW@1800RPM	<b>SECT.</b>  <b>A</b>	 Enriching Lives
---	--	------------------------------	--

S. NO.	PARAMETER	UNIT	VALUE
1.20	Lubricating oil grade	--	SAE15W40, CI4
1.21	Lubricating pump type	--	Positive displacement G-Rotor
1.22	Maximum Lubricating oil flow ( @ 1765 Lube oil Pump Speed with 3 bar oil pressure & 90° ± 10°C (194 ± 50 °F) Oil temperature)	lpm	44
1.23	Maximum Lubricating oil pressure	bar	5.5
1.24	Lubricating oil change period (* First oil change at 50 hrs.)	hours	250
1.25	Maximum Oil temperature	°C (°F)	125 (257)
1.26	Lubricating oil consumption (As per KOEL std. test cycle and test procedure. Subject to change.)	% of fuel consumption	0.15
1.27	Fuel used	--	Ultra-Low Sulfur Diesel (ULSD)
1.28	Fuel Injection type	--	Mechanical PLN, Inline Pump
1.29	Fuel filter	--	0.6 liter Single bowl
1.30	Pre-filter	--	0.8 liter Single bowl
1.31	Maximum allowable back pressure of exhaust system at rated brake power (at exhaust diffuser outlet)	kPa G	10 ± 1
1.32	Maximum allowable air temperature in inlet manifold	°C (°F)	50 (122)
1.33	Maximum allowable air temperature at CAC outlet	°C (°F)	48 ± 2 (118.4 ± 35.6)
1.34	Maximum allowable pressure drop across CAC	kPA	< 10
1.35	Maximum temperature rise from ambient to inlet of turbocharger	°C (°F)	To be updated
1.36	Maximum exhaust temperature (at exhaust turbine outlet)	°C (°F)	680 (1256)
1.37	Max. air inlet restriction - Clean air cleaner - Used air cleaner	mm H <sub>2</sub> O	200 500
1.38	Maximum inlet air flow	(m <sup>3</sup> /min)	4.8

Prepared by  <b>NRS</b>	Checked & approved by  <b>VMT/ YVA</b>	Revision No.  <b>00</b>	Date  <b>26/10/2018</b>	Issued by  <b>CRE / KOEL</b>
-------------------------------	--	-------------------------------	-------------------------------	------------------------------------

No. : <b>T4.SPEC.601.3.B</b> SHEET NO. : A/3		<b>BROAD SPECIFICATIONS</b>  <b>4R810TA2</b> 47.8kW@1800RPM	<b>SECT.</b>  <b>A</b>	 Enriching Lives
<b>S. NO.</b>	<b>PARAMETER</b>	<b>UNIT</b>	<b>VALUE</b>	
1.39	Maximum exhaust gas flow	(m <sup>3</sup> /min)	15.9	
1.40	Cooling Fan air flow (in open condition)	(m <sup>3</sup> /min)	174	

Prepared by  <b>NRS</b>	Checked & approved by  <b>VMT/ YVA</b>	Revision No.  <b>00</b>	Date  <b>26/10/2018</b>	Issued by  <b>CRE / KOEL</b>
-------------------------------	--	-------------------------------	-------------------------------	------------------------------------